TECHNICAL DATA SHEET



CERAMSTAK

ANTIADHESIVE SPRAY CERAMIC BASED NANO-TECHNOLOGY

CHARACTERISTICS

Rase. Micronized ceramic in synthetic vehicle Propellant: Denaturated and odourless hydrocarbon

Appearance: Dry white film 1500°C. Temperature resistance: Drying surface time: 5 minutes

Silicone free CFC free

APPLICATIONS

Anti-spatter for welding torches.

Suitable for: MIG/MAG torches, laser and plasma cut, automatic welding machines. Lubricant for high temperature.

PROPERTIES

- It resists many hours
- Protect torches from wear
- Reduces torches cleaning time
- Fast drying
- Handy format in spray
- Reduces cans waste thanks to 500 ml format
- Economy size: + 25% compared to 400 ml
- Good electric insulator
- Good thermal conductor
- Improves productivity

DESCRIPTION

CERAMSTAK is a good anti-spatter to protect the nozzle of the torch against the drops adhesion. It lasts many hours (until 8 hours) and it has a high anti-adhesive power superior to usual silicone free anti-spatters because it resists to high temperatures. CERAMSTAK is also a good lubricant, it leaves a thin dry film that improves the testing, prevents friction and reduces strain. It could be used to lubricate working tables, furnaces, foundry rails and whenever is required a dry lubricant for high temperatures.

INSTRUCTIONS OF USE

Apply on clean surfaces to treat, dry and degrease well. Shake for 1 minute at least, during the application shake occasionally the product to keep it homogeneous. Spray it from 15 cm distance and deposit a thin film. After the use overturn the can and spray the product few seconds to dodge the obstruction of the valve.

PACKAGING

Spray Aerosol ml 500 Box 12 Aerosol Product Code 11611/05

Revision date 01.08.2016

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product. CERTIFIED QUALITY

> Tel: +39 0444 649766 Fax: +39 0444 440018

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

SILICONI COMMERCIALE® Technical data- sheet



UNI EN ISO 9001:201

email: info@siliconi.it

www.siliconi.it