

## ROCUT CUTTING OIL SPRAY

### CHARACTERISTICS

Base:	Mixture of oils and additives with high cooling power
Propellant:	Denatured and odourless hydrocarbons (VOC Free)
Appearance:	Yellow viscous liquid
CFC free	

### PROPERTIES

- For any ferrous and non-ferrous metal
- It has anti-rust properties

### DESCRIPTION

ROCUT is a high quality and high performance cutting oil.

It is specially formulated to be applied during milling, cutting, drilling, threading, etc...

It can be used to work any ferrous and non-ferrous metal and related alloys as steel with high and medium content of carbon, nickel and its alloys, manganese, and steel 18/10.

It is a protective against rust.

The little pipe allows to reach all parts.

It can be eliminated with water.

### INSTRUCTIONS OF USE

Spray the product from 10 cm distance over the surfaces to be worked.

### PACKAGING

Spray Aerosol ml 400

Box 12 Aerosol

Product Code 13010/04



Revision date 02.08.2016

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

**SILICONI COMMERCIALE®** Technical data- sheet

